



RESIKON RESIKOT

ALL IN ONE COAT

TECHNICAL DATA SHEET

INTRODUCTION	RESIKOT is an acrylic polymer coating designed to give following properties: <ul style="list-style-type: none">• Elastomeric, Waterproofing and Temperature Shielding• Crack filling and Aesthetic Coating
AREA OF APPLICATION	It has very good bonding properties with horizontal as well as vertical surfaces of cement and concrete.
SPECIAL FEATURES	<ul style="list-style-type: none">• Single component environment friendly.• Resistance to water ingress.• Highly flexible with 2mm crack bridging properties.• Easy to apply by brush or roller or any other coating tools.• Bonds well with all types of concrete, brickwork, etc.• Can be tinted to wide range of colors for aesthetic appeal but it is recommended to use as it is to get good reflection of sunlight.• UV and weather resistant.• Temperature shielding.• Easy to clean.
TYPICAL PROPERTIES	Appearance : White consistent paste % Total Solids : 48 ± 1 Viscosity by Brookfield at 30°C[cps] : 8000 -9000 Spindle No. 5 & RPM 60 pH : 07 - 09 Bulk Density : 1.16 - 1.18
MECHANICAL PROPERTIES	Resistance to water : Excellent Drying time (pure material) : 30 - 40 minutes Tensile strength [Mpa] : 2 - 2.5 % Elongation : 150 -200

COVERAGE	<p>Wall 25 - 30 sq ft /kg for 3 coats. Terrace 15 – 20 sq ft/kg for 3 coats Coverage may vary from surface to surface depending upon the texture, porosity of the surface.</p>
PACKING	1 kg, 5 kg, 20 kg
STORAGE	<p>Shelf life of RESIKOT is twelve (12) months from the date of manufacture but can be stored for Twenty four (24) months in a tightly closed container in a cool and dry place. Keep away from direct sunlight and heat.</p>
SAFETY DATA	<p>HEALTH HAZARD: RESIKOT is nontoxic in nature. It is recommended to take necessary precaution, which one would take while handling alkaline substance. Use rubber hand gloves, splash goggles etc. Direct contact with any part of the body, especially with eyes must be avoided. In case of contact or splash into eyes, wash with water immediately and consult a physician. FIRE HAZARD: By itself it cannot catch fire. If comes in contact with alkali heat and fumes can get generated.</p>
DISCLAIMER	<p>This information is given to the best of our knowledge. There is no legally binding assurance of certain properties for a specific purpose. The customer is responsible for determining whether the product and Information provided here is appropriate for his use. It is the sole responsibility of the customer to ensure that any proprietary rights and existing laws and legislation are observed.</p>

ANUVI CHEMICALS LIMITED (AN ISO 9001: 2015 COMPANY)
Sales office: 205/210/211, Narmada, Laxmi Industrial Premises,
Pokharan Road No.1, Vartak Nagar, Thane - 400 606,
Maharashtra. India.
Tel.:+91-22-25855379 / 25855714 **Website** www.resikon.com

